




















# WOVEN FLOORING

BY DICKSON

## TECHNICAL SPECIFICATION

### INFORMATIONS TECHNIQUES

		STANDARD NORME	BE EASY	ALLURE, BE TWEED, COSMOS, ECUME, ELEGANCE, EMPREINTE, MIRAGE
	Use classification	EN ISO 10874	33 Heavy Commercial / 33 Commercial intensif	
		ASTM D 5252	5/5	
	Fire classification	EN 13501-4	Cfl s1	
		ASTM E 648	1st Class / Classe 1	
		ASTM D2859	Methamine Pill Test - CSPC FF1-70: pass	
	Optical smoke density	ASTM E 662	< 450	
	Soundproofing	ISO 10140-3	18 dB	
		ASTM E 492	IIC 59	
	Sound absorption coefficient <i>cw</i>	EN ISO 354	0,05	
	Roll width	EN 426	-	200 cm / 78,74"
	Roll length	EN ISO 24341	-	25 m / 9,84"
	Tile packaging and size	EN 994	50 x 50 cm - 19,69 x 19,69" - Box of 16 tiles / boîte de 16 pièces (4 m <sup>2</sup> / 4 sq.m. / 43,06 sq ft)	
	Thickness	ISO 1765	3,7 mm / 0,146"	4 mm / 0,157"
	Weight	ISO 8543	3,55 kg/m <sup>2</sup> / 84,24 lb/ft <sup>2</sup>	
	Castor chair	EN 985-A	Intensive use / Usage intensif	
	Body voltage	ISO 6356	< 2 kv	
	Residual indentation	EN ISO 24343-1	< 0,2 mm / < 0,08"	
		ASTM F 914	0,18 mm / 0,007"	
	Static load	ASTM F970	Conform 250 Psi / Conforme à 250 Psi	
	Compression recovery		95%	
	Fraying	EN 1815	Frayproof / Résistant à l'effilochage	
	Thermal resistance	ISO 8302	Suitable for underfloor heating / Adapté au chauffage au sol	
	Dimensional stability	ISO 2551	< 0,1%	
	Colour fastness to light	ISO 105 B02	8/8	
		AATCC 16 E	5/5	
	Colour fastness to weather	ISO 105 B04	5/5	
	Slip resistance dry (dynamic coefficient of friction)	EN 13893	$\mu > 0,3$	
		ASTM C 1028	0,81	
	Slip resistance wet (ramp test with oil)	DIN 51130	R9	
		ASTM C 1028	0,61	
	CE Certification	EN 14 041	0493-CPD-0101	
	Floorscore Certification (rolls + tiles)	SCS-EC10.2-2007	SCS - FS - 02719	

According to EN 1307 standard / Selon la norme EN 1307

Edition 07/2020 - SAS DICKSON CONSTANT - capital 12.640.000 euros - 381 347 970 R.C.S. Lille Métropole  
\* See general warranty conditions on www.dickson-constant.com / voir conditions générales de garantie sur www.dickson-constant.com



10 rue des châteaux  
BP 109 - Z.I. la Pilaterie  
59443 Wasquehal Cedex  
France  
Tél. + 33 (0)3 20 45 59 59  
www.dickson-constant.com



Performance fabrics for:  
solar protection  
outdoor furniture  
indoor furniture  
marine furnishing  
flooring